



SUITE

TERRACE

TOWN HOUSE

LEVEL 2

6.90

84.55

6
[152]

PERLITE CANT STRIP

TO BE SECURED USING 3/8" SCREWS.
MINIMUM 2 PER PANEL

EXTERIOR

CONTINUOUS INTAKE/EXHAUST/VENTILATION
PERFORATED GRILLE

CLADIFY PANEL

SEMI-RIGID INSULATION

METAL FLASHING BY OTHERS

SEALANT

FACTORY BONDED CORNER

CLADIFY PANELS

METAL ANGLE
SUPPORTING PANELS W/ POP RIVETS AS REQ'D
NOTE: ANGLE AND HORIZONTAL
SUPPORT TO BE CONFIRMED BY ENG.

INTERLOCKING CHANNEL
FIELD FASTENED TO
PANEL USING POP RIVETS
FIELD FASTENED THRU
SHIM AND INTO EVERY CHANNEL
USING TEK SCREWS AS REQ'D

SEALANT

SHOP INSTALLED METAL ANGLE
PROFILE CREATES SHADOW REVEAL
HIDES EXPOSED HONEYCOMB EDGE

THERMALLY BROKEN BRACKET
FIELD FASTENED TO EVERY CHANNEL
FIELD FASTENED THRU SHIM AND
INTO CONCRETE USING CONCRETE PINS

ANGLE
SPACED NOT MORE THAN 2 FT.

VAPOUR BARRIER

FACTORY BONDED CORNER

METAL FLASHING

CONTINUOUS DRAINAGE/VENTILATION
PERFORATED GRILLE