

BALCONY

ANGLE SUPPORTING CLADIFY PANELS W/ POP RIVETS AS REQUIRED, SPACED NOT MORE THAN 2 FT.

FACTORY BONDED CORNER

THERMAL STOP SHEET

SEALANT AND BACK ROD

5% SLOPE

SEALANT AND BACK ROD.

ADJUSTABLE BRACKET AS REQUIRED, SPACED NOT MORE THAN 2 FT.

WATER PROOFING MEMBRANE COORDINATE WITH SUBTRADES REQUIRED

SEMI-RIGID MINERAL WOOL INSULATION

FACTORY BONDED CORNER

CLADIFY PANELS

FACTORY BONDED CORNER

ADJUSTABLE BRACKET SUPPORTING CLADIFY PANELS W/ POP RIVETS AS REQUIRED, SPACED NOT MORE THAN 2 FT.

CAULKING

FACTORY BONDED CORNER

ADJUSTABLE BRACKET AS REQUIRED, SPACED NOT MORE THAN 2 FT.

FACTORY BONDED CORNER

SEALANT AND BACKER ROD WEEPHOLE @ 600mm (24")

ANGLE SUPPORTING CLADIFY PANELS W/ POP RIVETS AS REQUIRED, SPACED NOT MORE THAN 2 FT.

CAULKING

CAULKING

CAULKING

TO BE SECURED USING 3/8" SCREWS. MINIMUM 2 PER PANEL

CEILING BRACKET SYSTEM AS REQUIRED, SPACED NOT MORE THAN 2 FT.

ANGLE SUPPORTING CLADIFY PANELS W/ POP RIVETS AS REQUIRED, SPACED NOT MORE THAN 2 FT.

CAULKING

CAULKING

THERMALLY BROKEN SYSTEM AS REQUIRED, SPACED NOT MORE THAN 2 FT.

